

# EnviroFold Loft Ladder



[Representative image of product]

## Product Description

The EnviroFold is the contractor's choice of loft ladder being both quick to install and a snug fit between standard UK joists. The thickly insulated trapdoor is finished in white and sprung counterbalanced for smooth operation. Suitable for ceiling heights up to 2.8m the innovative design takes up no space in the attic. A continuous air seal, and extra-thick wooden frame combine with a 33mm thick trapdoor to achieve a tested U-value of 1.11 W / m<sup>2</sup>K. The deep anti-slip treads are morticed into the stiles using traditional methods for maximum comfort. This quick installation kit comes complete with angled feet, a handrail for added security and an operating pole and hook. Precision manufactured in Europe's Clean Tech Valley using renewable energy and PEFC sustainably sourced timber.

## Features

- Tested U-Value of 1.11W/m<sup>2</sup>K for improved insulation and reduced heat loss
- Supplied with slip-resistant feet and handrail for extra security
- 33mm deep insulated white trapdoor with push/pull lock
- 18mm thick frame features continuous seal that keeps cool drafts out
- Slip-resistant mortice and tenon secured treads, only final assembly required for quick installation
- Requires no headroom or storage space in the loft
- Manufactured using PEFC sustainably sourced timber
- Manufactured using 100% renewable energy

## Specifications

- Brand: TB Davies
- Warranty: 1-year
- Max Load: 150kg
- Standard: EN14975
- Material: Timber
- Commodity Code: 44189990
- Country of Origin: AT
- Recommended Usage: Regular

## Frame Dimensions

- Distance Between Treads: 235mm
- Tread Width: 345mm
- Tread Depth: 80mm
- Tested U-Value: **1.11W/m<sup>2</sup>K**
- Insulated Hatch Thickness: 33mm
- Frame/Stile/Tread: Plywood/Nordic Spruce/Nordic Spruce

## Availability & Delivery

Stock item. Delivery next day.

## EnviroFold Loft Ladder

### Product Dimensions

SKU	Treads /Sections	Aperture L x W (mm)	Frame Size L x W (mm)	Max. Floor to Ceiling (mm)	Max. Swing Clearance Length (mm)	Going (mm)
1530-005	4 x 3	1200 x 550	1190 x 540	2800	550	1200

### Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m <sup>3</sup> )	Gross Weight (kg)
1530-005	5060169480971	1250	650	400	0.325	27.5

### Optional Extras / Spare Parts

SKU	Description
1530-005C	EnviroFold Loft Ladder Fixings Bag

**Packaging Material:** Cardboard Box