



Saferstep LH

These flexible ladders ensure safe access to shelving and can be adapted to the required height.

Product description

- The hook-on shelf ladders have two hooks for the guiderail and additional hooks for vertical storage on the shelf.

Product features

Coating: anodised
 Connection between stiles and rungs/stiles: flanged
 Load: max. 150 kg
 Material: aluminium
 Product type: Flanged hook-on shelf ladder with treads
 Tread depth: 80 mm
 Type of rungs/treads: Safer Step
 Vertical distance between each rung/tread: 265 mm



Hints and special features

Please quote the distance between the floor and the top edge of the tubular rail when ordering!
 Complies with EN 131 Professional.

Product variants

Order number	Number of treads	Transport dimensions	Vertical hook-on height	maximum vertical hook-on height	minimum vertical hook-on height
1041356	6	1.940 mm × 423 mm × 73 mm	=1,31m--=1,78 m	= 1.78 m	= 1.31 m
1041358	8	2.500 mm × 423 mm × 73 mm	=1,79m--=2,28 m	= 2.28 m	= 1.79 m
1041360	10	3.060 mm × 423 mm × 73 mm	=2,29m--=2,82 m	= 2.82 m	= 2.29 m
1041362	12	3.620 mm × 423 mm × 73 mm	=2,83m--=3,35 m	= 3.35 m	= 2.83 m
1041364	14	4.180 mm × 423 mm × 73 mm	=3,36m--=3,87 m	= 3.87 m	= 3.36 m