

BSEN131 Glassfibre Stepladders



- ✓ Certified to BSEN131
- ✓ Non-conductive so is ideal to use where electrical hazards exist
- ✓ Unique strengthening beam incorporated into non-slip treads, rubber feet and aluminium side arms prevents slips and twists as there are no tapes to snap, or flimsy arms to break
- ✓ Rigid box section back legs with additional cross braces and 'k' straps for increased strength and stability. Back legs of 10 and 12 tread are reinforced.
- ✓ Lightweight and easy to carry
- ✓ Plastic tool tray to hold tools and equipment while working

Treads - Swingback	3	4	5	6	7	8	10	12
Open Height	0.55m	0.77m	0.99m	1.22m	1.44m	1.70m	2.11m	2.54m
Closed Height	0.59m	0.85m	1.10m	1.34m	1.58m	1.81m	2.29m	2.77m
Product Weight	2.70kg	3.80kg	4.90kg	5.80kg	6.70kg	7.60kg	11.50kg	12.50kg

Treads - Platform	3	4	5	6	7	8	10	12
Open Height	1.23m	1.44m	1.67m	1.89m	2.10m	2.31m	2.73m	3.17m
Platform Height	0.59m	0.82m	1.04m	1.26m	1.48m	1.69m	2.11m	2.56m
Closed Height	1.33m	1.56m	1.80m	2.04m	2.27m	2.51m	3.00m	3.47m
Product Weight	5.80kg	6.70kg	7.80kg	8.80kg	9.60kg	10.70kg	13.60kg	15.50kg



BSEN131



150KG MAX
PERMISSIBLE LOAD

LYTE
LADDERS • TOWERS